EDL-250/SW

Order No. 1000763

EDL-250/WS



Order No. 0162290

Weatherproof PA sound projector

- 100 V transmission technology
- Weatherproof plastic housing
- Connection cable with 3 power taps

Model	EDL-250/SW	EDL-250/WS
Power rating (RMS)	30/15/7.5 W	30/15/7.5 W
Frequency range	125-15,000 Hz	125-15,000 Hz
SPL	101 dB/W/m	101 dB/W/m
Dimensions	Ø 180 mm x 200 mm	Ø 180 mm x 200 mm
Weight	2.1 kg	2.1 kg




EDL-220/WS







• Pivoting mounting bracket



- 100 V transmission technology
- 2 speakers with polypropylene cone for bilateral
- Splashproof due to plastic housing with rubber seals
- Connection cable with 3 power taps
- Pivoting mounting bracket and screws made of stainless steel

Model	EDL-220/WS
Power rating (RMS)	20/10/5 W
Frequency range	120-20,000 Hz
SPL	94 dB/W/m
Dimensions	Ø 180 mm x 251 mm
Weight	2.76 kg



EDL-110/WS

Order No. 0161930





Weatherproof PA sound projector

- 100 V transmission technology
- 1 speaker with polypropylene cone
- Splashproof due to plastic housing with rubber seals and high-strength cable gland
- Connection cable with 3 power taps
- Stainless steel screws and pivoting mounting bracket

Model	EDL-110/WS
Power rating (RMS)	10/5/2.5 W
Frequency range	120-20,000 Hz
SPL	94 dB/W/m
Dimensions	Ø 180 mm x 270 mm
Weight	2 kg



EDL-255/WS

Order No. 0160860



PA sound projector

- \bullet 100 V transmission technology or 8 Ω operation
- 6-step power selector switch for 15/8/4/2 W/off or $8~\Omega$ operation
- White plastic housing with pivoting mounting bracket

Model	EDL-255/WS
Power rating (RMS)	15/8/4/2 W
Frequency range	100-15,000 Hz
SPL	92 dB/W/m
Dimensions	Ø 180 mm x 280 mm
Weight	2.59 kg

