

### RU-8012DB/5

Order No. 0259420

#### 2-channel diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute

Model	RU-8012DB/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-16,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 185 mm
Weight receiver	508 g

**There are restrictions or requirements within the EU.**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



### RU-8011DB/5

Order No. 0259200

#### Diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute

Model	RU-8011DB/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-16,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 185 mm
Weight receiver	457 g

**There are restrictions or requirements within the EU.**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



### RU-8011D/5

Order No. 0259848

#### Diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels (114 channels)
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Auto-scan function
- Pilot tone squelch and noise mute

Model	RU-8011D/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	60-15,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 180 mm
Weight receiver	440 g

**There are restrictions or requirements within the EU.**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



### RU-850LTH/5

Order No. 0259560

#### Dynamic hand-held UHF PLL microphone transmitter

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Lock function/mute function
- Special design to reduce handling noise, structure-borne noise and acoustic feedback
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

Model	RU-850LTH/5
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	30 h
Audio frequency range	50-16,000 Hz
Max. sound pressure	148 dB
Dimensions	Ø 51 mm x 269 mm
Weight	242 g

**There are restrictions or requirements within the EU.**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

