Spottune OMNI REC recessed speaker: wireless 360° ceiling mount speaker for installation into suspended ceilings. The minimum mounting depth is 45 mm, power is supplied via standard ceiling outlet using the supplied junction box.

OMNI-REC/SW Order No. 1000660 OMNI-REC/WS











Spottune OMNI REC recessed speakers

- All-in-one smart speaker (built-in amplifier, audio filter and receiver)
- Easy plug-and-play installation via standard ceiling outlet
- Automatic linking and settings in pairing mode with LED status indication at initial operation via Spottune network audio streamer STREAM
- Consistent 360° sound radiation for a constantly pleasant sound experience, independent of the position in the room
- Well-balanced and clear sound at low volume
- Reliable and stable audio transmission in the frequency range of 1.9 GHz
- Closed full range speaker system



OMNI-REC/SW, OMNI-REC/WS	
50 W, class D amplifier	
50-15,000 Hz	
360° radiation	
~ 100-240 V/50-60 Hz/2 VA max.	
via standard ceiling outlet	
Ø 115 x 200 mm	
ceiling cutout: 155-160 mm	
mounting depth: 45-100 mm	
1.5 kg	
	50 W, class D amplifier 50-15,000 Hz 360° radiation ~ 100-240 V/50-60 Hz/2 VA max. via standard ceiling outlet Ø 115 x 200 mm ceiling cutout: 155-160 mm mounting depth: 45-100 mm

Central audio/music streamer for Spottune speaker systems





Order No. 1000606



Spottune STREAM audio streamer

- Central transmitter and receiver unit (high operating reliability due to DECT technology)
- 2 music zones can be controlled individually
- Microphone input for announcements
- Web-based DSP and control surface
- Spotify Connect

- USB port for music reproduction
- Different music contents can be played in separate
- Status monitoring of integrated speakers
- Announcements via all speakers using microphone

STREAM
wireless audio streamer
audio transmission: UHF band 1.8-1.9 GHz,
operating range: approx. 50-100 m, depending on
surrounding and place of application
Spottune speaker systems
~100-240 V/50-60 Hz via encl. power supply
230 x 45 x 200 mm
600 g
output for 1 or 2 music zones
inputs:
RJ45 (LAN),
3.5 mm jack (AUX IN),
3.5 mm jack (MIC IN)

Subwoofer extension for Spottune speaker systems





Spottune wireless smart subwoofers, as an addition to existing Spottune speaker systems for extending the bass reproduction.

- All-in-one smart subwoofer (built-in 200 W amplifier and receiver)
- 25 cm (10") bass speaker/driver of long excursion
- Closed cabinet design for optimum output power and extended bass reproduction
- Easy plug-and-play installation/connection to Spottune audio streamer STREAM
- Reliable and stable audio transmission in the frequency range of 1.9 GHz



Model	SUB/SW, SUB/WS
Power rating (RMS)	200 W, class D amplifier
Frequency range	20-200 Hz
Power supply	~ 100-240 V/50-60 Hz
Dimensions	540 x 200 x 360 mm
Weight	12.65 kg

MONACOR INTERNATIONAL INSTALLATION